

CHASSIS

Front: Independent H.O.S.S. (High-Performance, Off-Road, Stability, Suspension) System with twin alloy A-arms and coil-over springs for optimum off-road stability and control with available H.O.S.S. System with Bilstein® Position Sensitive Dampers.
Rear: Solid five-link rear axle H.O.S.S. (High-Performance, Off-Road, Stability, Suspension) System with coil-over springs for optimum off-road capability and durability with available H.O.S.S. System with Bilstein Position Sensitive Dampers.

Off-road capability	Two-door	Four-door
Ground clearance	8.4/11.6	8.3/11.5 (Base/35-inch tires)
Suspension travel front/rear (millimeters)	200/215 (Base) 240/261 (Badlands)	200/215 (Base) 240/261 (Badlands)
Approach angle (degrees)	35.5/43.2	35.5/43.2 (Base/35-inch tires)
Breakover angle (degrees)	21.1/29.0	20.0/26.3 (Base/35-inch tires)
Departure angle (degrees)	29.8/37.2	29.7/37.0 (Base/35-inch tires)
Ramp travel index (Badlands only) (Sta-Bar connected and disconnected.)	560/700	500/620 (Projected)
Maximum water fording (inches) (Based on Sasquatch package)	33.5	33.5

WHEELS

Series	
Standard	Base
Standard	Big Bend
Standard	Black Diamond
Optional	Black Diamond
Standard	Outer Banks
Standard	Badlands
Optional	Badlands
Standard	Wildtrak†
Standard	First Edition†

† Denotes Sasquatch Package

Sasquatch™ Package

Series	
Standard	Big Bend, Black Diamond, Badlands
Optional	Big Bend, Black Diamond, Badlands

TIRES *All dimensions measured in inches.*

Size (Diameter)	30	32	32	32	33	33	35
Size (Width)	255/70R16	255/75R17	255/70R18	265/70R17	285/70R17	285/70R17	315/70R17
Wheel Size	16x7	17x7.5	18x7.5	17x7.5	17x8	17x8	17x8.5
Tread Type	A/S	A/T	A/T	A/T	A/T	M/T	M/T
Supplier	Bridgestone	Bridgestone	Bridgestone	General Tire	BF Goodrich	Goodyear	Goodyear
Brand	Dueler H/T 685	Dueler A/T RH-S	Dueler A/T RH-S	General Grabber A/Tx	All-Terrain TA KO2	Territory	Territory
Series	Base	Big Bend	Outer Banks	Black Diamond	Badlands	Badlands Optional	Sasquatch Wildtrak First Edition

*All specifications subject to change.

